

Features

ANDROSCAN = mini barcode scanner + Scan Holder

**** With ANDROSCAN, it can make Android OTG smartphone become data collector. Plug and Play.**

**** Mini barcode scanner is with touch trigger. The operation is easy.**

**** Scan Holder can be used for different size of Android OTG devices. (from 4" to 6" size)**

**** Scan Holder with PU glue / sucker can be stuck on smart-phone strongly. PU glue is repeated used.**

**** Scan holder solves the issue for micro USB port in the bottom of phone.**

**** Scan holder H92P can provide power to mini barcode scanner.**

**** You don't need to remove Scan holder when in charge. You can charge the battery inside & smart-phone battery both through its micro USB port.**



Specifications :

Model Name	DC9257AP	DC9257AN
Engine	Ultra-long range CCD engine	

Performance Characteristics

• Light source	610nm~640nm Red LED	
• Depth of field	UPCA (13mil): 50mm~620mm EAN13 (13mil): 50mm~610mm	
• Scan speed	300 scans/sec	
• Best resolution	4 mil	
• Scan Angle	Pitch $\pm 60^\circ$ @ 0° Roll and 0° Skew Roll $\pm 30^\circ$ @ Pitch and 0° Skew Skew $\pm 60^\circ$ @ Roll and 0° Pitch	
• Interface	Micro USB	
• Print contrast	$\geq 30\%$	
• Symbologies	EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code 93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI	
• Scan Holder	with H92P (with battery) rechargeable Li-Ion 3.7V 900mAH	with H92N (without battery)

Electrical Characteristics

• Input voltage	5 V/DC $\pm 5\%$
• Current - operating	85 mA max

Physical Characteristics

• Dimension (L * W * H)	125 X 52.5 X 32.5 mm	
• Color of housing	Black	
• Weight	82 g +/- 5 g	60 g +/- 5 g

Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw