

Features

ANDROSCAN = mini barcode scanner + Scan Holder

**** With ANDROSCAN, it can make Android OTG smartphone become data collector.**

Plug and Play.

**** Mini barcode scanner is with touch trigger. The operation is easy.**

**** Scan Holder can be used for different size of Android OTG devices.
(from 4" to 6" size)**

**** Scan Holder with PU glue / sucker can be stuck on smart-phone strongly.
PU glue is repeated used.**

**** Scan holder solves the issue for micro USB port in the bottom of phone.**

**** Scan holder H92P can provide power to mini barcode scanner.**

**** You don't need to remove Scan holder when in charge. You can charge
the battery inside & smart-phone battery both through its micro USB port.**



Specifications :

Model Name	DC9257LP		DC9257LN
Engine	RIOTEC 2D engine		

Performance Characteristics

• Light source	625±10 nm LED		
• Depth of field	1D (20 mil Code 39) : 320 mm		
• Best resolution	1D (CODE39) ≥ 5mil 2D (PDF417) ≥ 6mil		
• Scan Angle	Tilt: 360° / Pitch ±50° / Skew ±50°		
• Interface	Micro USB		
• Print contrast	≥ 30%		
• Symbologies	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Code 93 Interleaved 2 of 5, Industrial 2 of 5, ISBN/ISSN, UCC/EAN-128, GS1 Databar, MSI PDF417, QR Code, Data Matrix		
• Scan Holder	with H92P (with battery) rechargeable Li-Ion 3.7V 900mAH		with H92N (without battery)

Electrical Characteristics

• Input voltage	5 V/DC ± 5%		
• Current - operating	230 mA		

Physical Characteristics

• Dimension (L * W * H)	125 X 52.5 X 32.5 mm		
• Color of housing	Black		
• Weight	82 g+/- 5 g		60g+/- 5 g

Environment

• Temperature-operation	0°C to 50°C		
• Temperature-storage	-10°C to 60°C		
• Humidity-operation	5% to 95% relative humidity, non-condensing		

Decode Zone

• 5 mil Code 39	60mm ~ 120mm		
• 13 mil UPC-A	45mm ~ 250mm		
• 20 mil Code 39	70mm ~ 320mm		
• 6.67 mil PDF417	40mm ~ 160mm		
• 10 mil DataMatrix	40mm ~ 160mm		
• 20 mil QR Code	40mm ~ 275mm		

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw

